



REVOLED-S

LOWBAY

Surface Mounted 153W LED High Bay Luminaire



Order Code : 3078196
 Product Code : RVL 153U 40TF00 LB 19K2

Product Data

Standard Features

Housing	: Aluminum profile
Diffuser	: Tempered glass with security film
Optic	: Miro silver reflector, wide angle
IP Grade	: IP65
Installation	: Surface mounted
Light Source	: Mid Power LED


Optical & Electrical Features

Power Consumption	: 152.6W
Final Luminous Flux	: 19202.2 lm
Efficacy	: 125.8 lm/W
Input Voltage	: 220-240 V
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Drive Current	: 600mA
Correlated Color Temperature	: 4000K
Color Rendering Index	: >80

Other Features & Conditions

Operating Temperature Range	: -20 °C/+45 °C
Operating Temperature Range With Emergency Kit	: +5 °C/+30 °C
Impact Resistance	: IK 09
Led Life Time - L70	: 60.000 hours @Ta= 45 °C

Photometric Curve




Optional Features

Correlated Color Temperatures	: 3000K, 5700K, 6500K
Emergency Kit Options	: 1, 3 hours
1-10V	: Yes
DALI Option	: Yes
KAM	: Yes

REVOLED-S LOWBAY

Surface Mounted 153W LED High Bay Luminaire

3078196 RVL 153U 40TF00 LB 19K2



Dimension (mm)

	a	b	h
Standard	1310	223	75
With Emergency Kit (1, 3 hrs.)	1310	223	75
DALI	1310	223	75
KAM *	1310	223	75


* KAM: Corridor Lighting Module

Weight (gr)

Standard	11.9
With Emergency Kit (1, 3 hrs.)	12.6, 12.8




Suspension Set




Busbar Mounting Set
Product Code : 3080654

a	b	c	Weight (gr)
62mm	48mm	162mm	312



Cable Tray and Wall Mounting Set
Product Code : 3080655

a	b	c	Weight (gr)
62mm	48mm	70mm	191



Wall-Mounted Suspension Set
With 10° Angular Adjustment Steps
Product Code : 3080656

a	b	c	Weight (gr)
110mm	89mm	290mm	-

- EAE, reserves the right to make changes without prior notice.



Revision date: 09.09.2016